

Cartridge:	10N0016 10N0217 18L0032	Cartridge Wt. New:	10N0217 29g Teal 10N0016 29 g Teal 18L0032 43g
OEM:	LEXMARK	Printer:	Z13,Z23,Z25,Z33,Z35,Z601,Z602 Z603,Z605,X75,X1110,X1130, X1140,X1150,X1155,X1180,X1185 X2230,X2240,X2250
Printhead Location:	Cartridge	Cartridge Type:	Sponge
Reliability:	* * *	Skill Level:	Average

Fill Here Vent Hole




Fig. 2.73

© Ausjet Ink Jet Supplies and Service Pty Ltd

COMMENTS

The 10n0016 is a high yield cartridge this means there is more ink in the 10N0016 than the 10N0217.

Refill both of them with the same amount of ink. This will make them both high yield cartridges.

These are black, sponge filled cartridge. Sponge is prone to drying out which may cause it to accept less ink than stated. Wash sponge out with alcohol if this occurs. Easy cartridge to refill.

REQUIREMENTS

- ♦ 10N0016 AND 10N0217 12 ml Appropriate Black Pigment.
- ♦ 18L0032 20ML of Appropriate Black Ink.
- ♦ 20 ml syringe with sharp needle
- ♦ small drill
- ♦ Head sealing tape and or cartridge clip.

REFILLING METHOD

STEP 1.

Enlarge the vent hole (see Fig. 2.73) enough to fit a syringe needle.

STEP 2.

Fill syringe with 12 ml ink and insert through central hole into sponge as far as it will go. Inject ink slowly into the cartridge making sure the needle is sitting on the bottom of the cartridge.

Cartridge may not accept more than 8-10 ml of ink.

Sit cartridge on paper towel after filling to absorb any drips.

STEP 3.

Use the Ausjet priming tool to remove air locks and prime the cartridge. Then do a DAB test. Then run 2 to 3 cleaning cycles and do a test print

STEP 4.

If not printing correctly gently steam or soak the printhead in hot water for 10–20 mins. Then repeat step3.