


Cartridge:	BC-22, BC-29F	Cartridge Wt. New:	Approx 90 g
OEM:	Canon	Printer:	BJC-2000,4200, BJC-4300, BJC-4310SP BJC-4550, BJC-4650 BJC-5000, BJC-5500
Printhead Location:	Cartridge	Cartridge Type:	Sponge
Reliability:	* * * *	Skill Level:	Average



© Ausjet Ink Jet Supplies and Service Pty Ltd

Fig. 2.21

COMMENTS

This is a four colour photo cartridge similar in appearance to the BC-20. Important: Read 'Nine Steps' and also study the section on 'Filling Colour Cartridges'.

REQUIREMENTS

- ◆ 0-12 ml Appropriate Black Ink. (Refer to Ausjet Ink Selector)
- ◆ 0-5 ml each Appropriate Cyan, Magenta, Yellow Inks. (Refer to Ausjet Ink Selector)
- ◆ 4 x 20 ml syringe with sharp 18g needle
- ◆ Plug removal tool
- ◆ HSC1000
- ◆ Print head sealing tape or print head clip.

REFILLING METHOD

STEP 1.

Soak the print head in HSC1000 for 10-20 mins.

Locate the four vent holes shown in the illustration and remove plugs. You may like to insert a clean toothpick into each hole to ensure you have the correct colour.

STEP 2.

Inject the appropriate colour ink very slowly into the cartridge making sure the needle is on the bottom of the cartridge. When you see a small amount of ink bubble to the top draw back a little on the syringe so as not to overfill.

STEP 3.

Let the cartridge stand on a paper towel to ensure excess ink has drained out.